

22.5 & 24.5hp

MFGC1700

Compact Tractors. Big Performance.



VISION INNOVATION LEADERSHIP QUALITY RELIABILITY SUPPORT PRIDE COMMITMENT



MASSEY FERGUSON

Massey Ferguson GC Series Tractors



Compact size with BIG tractor performance.

For both residential and professional operations, the MF GC1700 Series delivers across the board – from easier operation and greater comfort to reducing fatigue, improving safety and maximising productivity. The MF GC1700 Series tractors are designed to make light work of big jobs. Yet, their compact size and versatile handling mean they're ideal for hobby farmers,

landscapers, homeowners and residential contractors. With engines ranging up to 24.5hp and unmatched versatility, the MF GC1700 is easy to drive, and can handle everything from mowing, loading, general farm work and more. So if your workload demands a real tractor, check out the MF GC1700 Series. It delivers on every job, every time.



1. Engine features

- 3-cylinder liquid cooled engine
- Solid metal hood with tilt design and open/close handle for easy access to serviceable areas
- Radiator with removable mesh screen to shield radiator from debris and allow access for cleaning

2. Operator's area

- New ergonomic seat, designed to custom fit all profiles
- Uncluttered platform to ensure ample room for movement
- Hydraulic joystick located on right side of console, for easy access
- Safety lock-out lever prevents accidental joystick movement
- Cruise control engagement through push lever located on dashboard

3. Tyres

- A choice of either turf tyres when minimal ground disturbance is required or ag tyres for tougher jobs that require traction

4. Three point linkage

- A large three point linkage capacity of 540kg



5. Axles

- Robust front and rear axles to handle a wide range of accessories and front end loaders

6. Quality mowing decks

- 60 inch side discharge deck available for residential or commercial use

7. Dual hydrostatic control pedals

- Control pedals allow forward and reverse control for maximum comfort

8. Differential lock

- The differential lock can be easily engaged using the foot pedal. Combined with 4WD, it ensures consistent and reliable traction through tough and slippery conditions

9. Cruise control

- Newly designed cruise control
- Improves driving comfort
- Can result in better fuel efficiency





Model: MF GC1705 MF GC1715

Engine

Engine Power hp	22.5	24.5
PTO hp	18.7	19.6
Rated engine speed	2,600	3,000
Type	3-cylinder diesel	3-cylinder diesel
Displacement: in ³ (cc)	68.5 (1,123)	68.5 (1,123)
Cooling system	Liquid-cooled	Liquid-cooled
Fuel tank capacity: L	25	25

Transmission

Control	Dual foot pedal	Dual foot pedal
Hydrostatic	2 range w/cruise	2 range w/cruise
Forward speeds: km/h (mph)	0-14.7 (0-9.1)	0-14.7 (0-9.1)
Rear brakes	Wet disc	Wet disc

Rear PTO

Rear PTO kW (hp)	13.9 (18.7)	14.6 (19.6)
Type	Independent	Independent
Speed	540@2532	540@2829
Shaft	Fixed	Fixed
Configuration	6 spline	6 spline

Mid PTO

Type	Independent	Independent
Speed	2000@2476	2000@2947
Configuration	15 spline	15 spline

Hydraulics

Type of system	Open centre	Open centre
Total flow: L/min (gpm)	24.0 (6.3)	26.3 (6.8)
Factory joystick	Standard	Standard

3-Point Hitch

ASAE hitch	Cat. I	Cat. I
Rate of drop control	Standard	Standard
Lift capacity @ hitch point: kg (lbs)	540 (1,190)	540 (1,190)
Type of stabilisers	Turnbuckle	Turnbuckle
Type of link ends	Fixed	Fixed

Model: MF GC1705 MF GC1715

Operator Area

Platform-ROPS	Fixed	Fixed
Seat type	Coil spring	Coil spring
Seat belt type	Retractable	Retractable
Hood type	Flip-up	Flip-up

Dimensions With Turf Tyres

Overall length: mm (in)	2,480 (97.6)	2,480 (97.6)
Max width @ ear		
combo light: mm (in)	1,200 (47.25)	1,200 (47.25)
Maximum height over ROPS: mm (in)	1,850 (72.8)	1,850 (72.8)
Ground clearance: mm (in)	170 (6.7)	170 (6.7)
Wheelbase: mm (in)	1,450 (57.1)	1,450 (57.1)
Shipping weight: kg (lbs)	650 (1,433)	650 (1,433)

Deck Model: SSM60

Type

60" mid-mount rotary deck

General

Discharge type	Side
Number of blades	3 (overlapping)
Gearbox drive	Shaft
Speed	2000 rpm
Blade tip speed	18,856 rpm
Gauge wheels	4
Scalp rollers	3
Raise & lower actuation	Via 3pt linkage
Height control	Manual adjustment
Transport height	150 mm

Dimensions (mm)/Weight (kg)

Cutting width	1524 mm
Overall width	1900 mm
Weight	200 kg
Overall height	524 mm

Capacities

Gearbox	800 cc
---------	--------

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.